


## NOTES:

1. NON-TOWN OPERATED UTILITIES CAN BE PLACED IN A JOINT TRENCH.
2. MINIMUM SEPARATION REQUIREMENTS FROM PUBLIC UTILITIES APPLY WITHIN EASEMENTS AND PRIVATE PROPERTY.
3. UTILITY POLES SHALL BE PLACED A MINIMUM OF 2.5' FROM FACE OF CURB TO OUTSIDE EDGE OF THE POLE.

NOT TO SCALE


APPROVED BY	DATE	 <b>TOWN OF</b> <b>LOS GATOS</b> <i>EST. 1856</i>	STD. PLAN NO.
	NOVEMBER 2010		ST-200
TOWN ENGINEER			



**NOTES:**

- (A) CONCRETE CURB AND GUTTER SEE STD PLAN 210.
- (B) CONCRETE SIDEWALK SEE STD PLAN 216.
- (C) FOR PLANTER DETAIL SEE STD PLAN 217.
- (D) FOR MINIMUM PAVEMENT SECTIONS, MATERIALS AND COMPACTION REQUIREMENTS SEE SECTION 2, STREET DESIGN STANDARDS.

APPROVED BY	DATE	COLLECTOR TYPICAL STREET SECTION	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-201



## NOTES:

(A) CONCRETE CURB AND GUTTER. SEE STD PLAN 210. CURBS SHALL BE PROVIDED ON BOTH SIDES OF ROAD. GUTTER MAY BE OMITTED WITH TOWN ENGINEER APPROVAL.

(B) CONCRETE SIDEWALK. SEE STD PLAN 216. SIDEWALKS ON ONE SIDE MAY BE PROVIDED DEPENDING ON TOPOGRAPHICAL CONSIDERATIONS. SEE STD PLAN 217.


(C) FOR PLANTER DETAIL

(D) FOR MINIMUM PAVEMENT SECTIONS, MATERIALS AND COMPACTION REQUIREMENTS SEE SECTION 2, STREET DESIGN STANDARDS.

(E) PARKING TYPICALLY PROHIBITED ON BOTH SIDES OF ROAD. IF PARKING IS ALLOWED ON ONE SIDE OF ROAD, PAVEMENT WIDTH SHALL BE 34' MIN.

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF <b>LOS GATOS</b>	HILLSIDE COLLECTOR TYPICAL STREET SECTION	STD. PLAN NO.
<i>Kevin Johnson</i>	NOVEMBER 2010			ST-202
TOWN ENGINEER				



NOTES:


(A) CONCRETE CURB AND GUTTER  
SEE STD PLAN 210.

(B) CONCRETE SIDEWALK  
SEE STD PLAN 216.

(C) FOR PLANTER DETAIL  
SEE STD PLAN 217.

(D) SAWCUTTING REQUIRED FOR ALL EDGES OF  
EXISTING IMPROVEMENTS TO BE REMOVED.

APPROVED BY	DATE	LOCAL STREET TYPICAL SECTION	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-203




## NOTES:

- (A) CONCRETE CURB AND GUTTER. SEE STD PLAN 210. CURBS SHALL BE PROVIDED ON BOTH SIDES OF ROAD. GUTTER MAY BE OMITTED WITH TOWN ENGINEER APPROVAL.
- (B) CONCRETE SIDEWALK. SEE STD PLAN 216. SIDEWALKS ON ONE SIDE MAY BE PROVIDED DEPENDING ON TOPOGRAPHICAL CONSIDERATIONS.
- (C) FOR PLANTER DETAIL SEE STD PLAN 217.
- (D) FOR MINIMUM PAVEMENT SECTIONS, MATERIALS AND COMPACTION REQUIREMENTS SEE SECTION 2, STREET DESIGN STANDARDS.
- (E) PARKING TYPICALLY PROHIBITED ON BOTH SIDES OF ROAD. IF PARKING IS ALLOWED ON ONE SIDE OF ROAD, PAVEMENT WIDTH SHALL BE 30' MIN.

NOT TO SCALE

APPROVED BY	DATE		HILLSIDE LOCAL STREET TYPICAL SECTION	STD. PLAN NO.
	NOVEMBER 2010			ST-204
TOWN ENGINEER				






NOTES:

- (A) CONCRETE CURB AND GUTTER. SEE STD PLAN 210.
- (B) CONCRETE SIDEWALK. SEE STD PLAN 216.
- (C) FOR PLANTER DETAIL SEE STD PLAN 217.
- (D) CONCRETE SIDEWALK. SEE STD PLAN 216.

NOT TO SCALE

APPROVED BY	DATE	ST. PLAN NO.
	NOVEMBER 2010	
TOWN ENGINEER		ST-205







## NOTES:


NOT TO SCALE

- 1 ALL TRENCHES IN ROADWAY AREAS SHALL BE BACKFILLED AND PATCHED WITH TEMPORARY ASPHALT AT THE END OF EACH WORK DAY, UNLESS PERMISSION IS GRANTED TO DO OTHERWISE BY THE TOWN ENGINEER.
- 2 ALL TEMPORARY PATCHES ON TRENCHES SHALL BE PERMANENTLY PATCHED WITHIN 7 WORKING DAYS OF COMPLETION OF WORK WITHIN THE ROADWAY AREA.
- 3 SEE SECTION 2, FOR COMPACTION REQUIREMENTS
- 4 EXCEPT WHERE GALVANIZED PIPES IS USED, THE BACKFILL SHALL BE EITHER A SAND SLURRY (2 SACK MIX), BE CERTIFIED BY A TEST TO BE 95% COMPACTED OR THE CONTRACTOR UTILITY PROVIDE AND IS ON HAND DURING THE RESTORATION.

APPROVED BY	DATE	 PAVEMENT PATCHING DETAILS	STD. PLAN NO.
	NOVEMBER 2010		ST-207
TOWN ENGINEER			



**HAMMERHEAD**






**CUL-DE-SAC**

NOTE:

1. PARKING SHALL BE PROHIBITED ON ALL HILLSIDE TURNAROUNDS.


ROAD TYPE	(A)	(B)
RESIDENTIAL ST.	32'	42'
COMMERCIAL/ INDUSTRIAL ST.	55'	65'
HILLSIDE	26'	32'

APPROVED BY	DATE		STREET END OPTIONS AND TURNING CIRCLES	STD. PLAN NO.
	NOVEMBER 2010			ST-208
TOWN ENGINEER				



APPROVED BY	DATE	ST. PLAN NO.
	NOVEMBER 2010	
TOWN ENGINEER		ST-209

## BUS TROUTOUT DETAIL




## NOTES:

1. ALL RADII LESS THAN 100' SHALL USE FLEXIBLE WOOD OR METAL FORMS TO ELIMINATE ANGULAR POINTS AT 10' SECTION POINTS.
2. SAWCUT AND REMOVE 20 IN. (MIN.) STREET SECTION FOR CURB AND GUTTER INSTALLATION ON EXISTING STREETS.
3. 3/4" EXPANSION JOINTS TO BE PLACED AT DRIVEWAY SECTIONS, CURB RETURNS, CURB RAMPS & COLD JOINTS OR A MAX. OF 30' C/C. EXPANSION JOINTS SHALL PROTRUDE 1" BELOW THE BOTTOM OF GUTTER
4. THRU JOINTS SHALL BE PLACED ADJACENT TO CATCH BASINS, INLETS AT POINTS OF TANGENCY ON STREETS, AND AT ALLEY AND DRIVEWAY RETURNS. MAXIMUM SPACING SHALL BE 30' PRE-MOLDED JOINT FILLER, SHALL BE 1/2" WIDE AND CONFORM TO AASHTO DESIGN M213. DUMMY JOINTS SHALL BE PLACED EVERY 10'.
5. FINISHED WORK SHALL NOT VARY MORE THAN 1/8" IN GRADE AND 1/4" IN ALIGNMENT.
6. THE FINISHED CURB SHALL IMMEDIATELY BE SPRAYED WITH A TRANSPARENT CURING COMPOUND. CURB SHALL BE COVERED BY WATERPROOF PAPER OR PLASTIC MEMBRANE IN THE EVENT OF RAIN OR OTHER UNSUITABLE WEATHER. CURING TIME SHALL BE A MINIMUM OF 72 HOURS.
7. ALL CURB AND GUTTER SHALL BE PLACED ON A MIN. OF 4" AGGREGATE BASE CLASS II 95% MAX. COMPACTION ASTM D1557
8. #4 REBAR SHALL BE EXTENDED ALONG LENGTH OF THE CURB AND GUTTER
9. GUTTER PAN SLOPE SHALL NOT EXCEED 5% SLOPE AT PEDESTRIAN CURB RAMP ENTRY LOCATIONS. CONTRACTOR SHALL USE 1.2" (MAX) BETWEEN LIP OF GUTTER AND FLOWLINE AT THESE LOCATIONS.
10. ALL CONCRETE SHALL INCLUDE ONE (1) POUND OF LAMP BLACK PER CUBIC YARD OF CONCRETE.
11. ALL CURB AND GUTTER SHALL HAVE 2 #4 REBARS THE ENTIRE LENGTH AND EMBEDDED ON BOTH ENDS USING DOWELS (ONE DOWEL IN THE CENTER OF THE GUTTER, ONE DOWEL IN THE CENTER OF THE CURB.)

NOT TO SCALE

APPROVED BY	DATE	CONCRETE CURB AND GUTTER	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-210




### NOTES:

1. THE CONSTRUCTION NOTES OF STD. PLAN 210 APPLY TO CONCRETE VERTICAL CURB.

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS	CONCRETE VERTICAL CURB	STD. PLAN NO.
 Kevin Rofai	NOVEMBER 2010			ST-211
TOWN ENGINEER				




NOTES:

1. EXPANSION JOINTS WITH 1/2" x 12" SLIP.
2. DOWELS AT 20 FEET INTERVALS.
3. CONCRETE SHALL BE CLASS A.
4. ALL CONCRETE SHALL INCLUDE ONE (1) POUND OF LAMP BLACK PER CUBIC YARD OF CONCRETE.


NOT TO SCALE

APPROVED BY	DATE		CONCRETE VALLEY GUTTER	STD. PLAN NO.
	NOVEMBER 2010			ST-212
TOWN ENGINEER				




NOT TO SCALE

APPROVED BY	DATE		CONCRETE CURB TAPER	STD. PLAN NO.
	NOVEMBER 2010			ST-213
TOWN ENGINEER				



### EXTRUDED CONCRETE CURB




### SPACING OF ANCHOR BARS

#### NOTES:

1. DUMMY JOINTS SHALL BE PLACED NOT TO EXCEED 15 FT ON CENTER. THRU JOINTS SHALL BE PLACED ONLY AT POINTS OF TANGENCY ON STREET, ALLEY, AND DRIVEWAY RETURNS AND WHERE THRU JOINTS OCCUR IN THE PAVEMENT SLAB.
2. AT THE CONTRACTOR'S OPTION CONCRETE CURBS MAY BE ANCHORED TO THE EXISTING PAVEMENT EITHER BY PLACING STEEL TIE BARS 1 FOOT ON EACH SIDE OF EVERY JOINT, OR BY USING AN ADHESIVE.

NOT TO SCALE


APPROVED BY	DATE	CONCRETE EXTRUDED CURB	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-214



## NOTES:


1. CONTRACTION JOINTS OF ONE OF THESE TYPES SHOWN ABOVE TO BE PLACED 10' C/C. COMPLETELY SEVER THE STRUCTURE TO THE POINTS SHOWN. JOINTS MAY BE MADE BY INSERTING MIN. 3/16" BITUMINOUS FILLER DUMMY JOINTS. JOINTS SHALL BE CLEANED AND EDGED.
2. FINISHED WORK SHALL NOT VARY MORE THAN 1/8" IN GRADE AND 1/4" IN ALIGNMENT.
3. EXPOSED SURFACES SHALL BE LIGHT BROOM FINISH.
4. SIDEWALKS BEHIND ROLLED CURBS SHALL BE A MINIMUM OF 6" THICK.
5. CONCRETE SHALL INCLUDE ONE (1) POUND OF LAMP BLACK PER CUBIC YARD OF CONCRETE.
6. #4 REBAR SHALL BE EXTENDED ALONG LENGTH OF GUTTER.

NOT TO SCALE


APPROVED BY	DATE		CONCRETE ROLLED CURB	STD. PLAN NO.
	NOVEMBER 2010			ST-215
TOWN ENGINEER				

1/2" FULL DEPTH  
EXPANSION JOINT EVERY  
30'. MATCH CURB.

SCORE MARK  
1/4" DEEP, 1/8" WIDE  
5' SECTIONS



### PLAN VIEWS



2 #4 REBARS ENTIRE LENGTH OF REPLACEMENT SECTION AND DOWELS EMBEDDED 4" INTO EXISTING SIDEWALK ON BOTH ENDS AND EXTENDING 8" MIN INTO EXISTING NEW CONCRETE. EXPANSION JOINTS SHALL ALSO BE DOWELED AS DESCRIBED.

4" AGGREGATE BASE  
CLASS II, 95% MAX.  
COMPACTION ASTM D1557



### NOTES:

### TYPICAL SECTION


1. SIDEWALKS SHALL BE A MINIMUM OF 4" THICK, AND SHALL BE CLASS A PORTLAND CEMENT CONCRETE.
2. FULL EXPANSION JOINTS SHALL BE PLACED TO MATCH THOSE PLACED IN ADJACENT CURB & GUTTER, WITH MAXIMUM SPACING OF 30 FEET.
3. SUBGRADE SHALL HAVE 95% MAXIMUM COMPACTION ASTM D1557
4. SIDEWALK SHALL BE AT LEAST 6" THICK BEHIND RESIDENTIAL DRIVEWAYS AND BEHIND ROLL-CURB AND 8" THICK BEHIND COMMERCIAL DRIVEWAYS.
5. THE FINISHED SIDEWALK SHALL BE SPRAYED WITH A TRANSPARENT CURING COMPOUND COVERED BY WATERPROOF PAPER OR PLASTIC SHEETING IN THE EVENT OF RAIN OR OTHER INCLEMENT WEATHER. CURING TIME SHALL BE FOR A MINIMUM OF 72 HOURS.
6. ALL JOINTS SHALL BE CLEANED AND EDGED WITH AN EDGER HAVING A 1/4" RADIUS.
7. SIDEWALK AND PLANTER STRIP WIDTHS SHALL CONFORM TO DIMENSIONS SHOWN IN APPROPRIATE STREET CROSS SECTION DETAIL.
8. THE WIDTH OF SIDEWALKS DIRECTLY BEHIND CURB WITHOUT PLANTER SHALL BE A MIN. OF 5' FROM BACK OF CURB.
9. CONCRETE SHALL INCLUDE ONE (1) POUND OF LAMP BLACK PER CUBIC YARD OF CONCRETE.
10. EXPOSED SURFACES SHALL BE A LIGHT BROOM FINISH.

NOT TO SCALE

APPROVED BY	DATE		CONCRETE SIDEWALK	STD. PLAN NO.
	NOVEMBER 2010			ST-216
TOWN ENGINEER				




6" PORTLAND  
CEMENT CONCRETE  
CLASS "A"  
1 LB LAMP BLACK  
PER CUBIC YARD OF  
CONCRETE



6" CLASS II AGGREGATE BASE, 95% MAX. COMPACTION ASTM D1557

NOT TO SCALE

APPROVED BY	DATE	PARKING BAY DETAIL	STD. PLAN NO.
	NOVEMBER 2010		
REGIN ROFANI TOWN ENGINEER			ST-217




## CURB TRANSITION DETAIL

- (A) EQUALS WIDTH OF DRIVEWAY AT PROPERTY LINE, (14' MIN. - 30' MAX. RESIDENTIAL & 25' MIN.-30' MAX. COMMERCIAL)
- (B) 1/2" WIDE FULL DEPTH EXPANSION JOINT.
- (C) FULL DEPTH EXPANSION JOINT IF (A) IS 15' OR GREATER.
- (D) DRIVEWAY TO BE SURFACED WITH ASPHALT OR CONCRETE.
- (E) DRIVEWAY CONCRETE SHALL BE A MIN. OF 6" THICK FOR RESIDENTIAL & 8" THICK FOR COMMERCIAL & IS TO BE PLACED ON A MIN. OF 4" CLASS II AGGREGATE BASE 95% MAX. COMPACTION ASTM D1557, OVER COMPACTED SUBGRADE.
- (F) ALL CONCRETE SHALL BE CLASS A, PER CALTRANS SPECIFICATIONS, WITH 1 LB. (MIN.) LAMP BLACK PER CUBIC YARD.
- (G) SAWCUT & REMOVE 20 FT. (MIN.) STREET SECTION FOR DRIVEWAY INSTALLATION IN EXISTING STREETS.
- (H) ALL WORK SHALL CONFORM TO CURRENT ADA REQUIREMENTS.

NOT TO SCALE

APPROVED BY	DATE		CONCRETE DRIVEWAY WITH PLANTER	STD. PLAN NO.
	NOVEMBER 2010			ST-218
TOWN ENGINEER				


SEE DETAIL  
BELOW




## CURB TRANSITION DETAIL



- (A) EQUALS WIDTH OF DRIVEWAY AT PROPERTY LINE. MINIMUM WIDTH = 14'.
- (B) 1/2" WIDE FULL DEPTH EXPANSION JOINT.
- (C) FULL DEPTH EXPANSION JOINT IF (A) IS 15' OR GREATER.
- (D) DRIVEWAY TO BE SURFACED WITH ASPHALT OR CONCRETE.
- (E) DRIVEWAY CONCRETE SHALL BE A MIN. OF 6" THICK FOR RESIDENTIAL AND 8" THICK FOR COMMERCIAL AND IS TO BE PLACED ON A MINIMUM OF 6" CLASS II AGGREGATE BASE 95% MAXIMUM COMPACTION ASTM D1557, OVER COMPACTED SUBGRADE.
- (F) ALL CONCRETE SHALL BE CLASS A, PER CALTRANS SPECS, WITH 1 LB. (MIN.) LAMP BLACK PER CUBIC YARD.
- (G) ALL WORK SHALL CONFORM TO CURRENT ADA REQUIREMENTS.

NOT TO SCALE

APPROVED BY	DATE		CONCRETE DRIVEWAY WITHOUT PLANTER	STD. PLAN NO.
	NOVEMBER 2010			ST-219
TOWN ENGINEER				



## PLAN




TACTILE WARNING BAND (SECTION)  
N.T.S.



## SECTION A-A

- (A) ALL CURB RAMPS SHALL COMPLY WITH THE CURRENT AMERICAN DISABILITIES ACT.
- (B) INSTALL 12" TACTILE WARNING BAND AROUND THE RAMP PERIMETER.
- (C) 3/8" EXPANSION JOINT.
- (D) CONCRETE CURB AND GUTTER, SEE STD. DETAIL 210.
- (E) CURB RAMPS SHALL NOT BE POURED INTEGRAL WITH SIDEWALK AND SHALL BE ISOLATED BY EXPANSION JOINT MATERIAL ON ALL SIDES, BUT NOT AT END OF RAMP ADJACENT TO ROADWAY. CURB & GUTTER ARE TO BE INTEGRAL WITH RAMP.
- (F) CONCRETE SIDEWALK, SEE STD. PLAN 216.
- (G) EXPOSED SURFACES SHALL BE A MEDIUM BROOM FINISH. CURB RAMPS EXHIBITING A RUNNING SURFACE SLOPE FROM 5% TO 6.67% ARE REQUIRED TO HAVE A TRUNCATED DOME DETECTABLE WARNING SURFACE OVER THE FULL WIDTH AND DEPTH OF THE RAMP.
- (H) MAXIMUM SLOPES OF ADJOINING GUTTERS, THE ROAD SURFACE IMMEDIATELY ADJACENT TO THE CURB RAMP AND CONTINUOUS PASSAGE TO THE CURB RAMP SHALL NOT EXCEED 5% WITHIN 4' OF THE TOP OR BOTTOM OF THE CURB RAMP.

NOT TO SCALE

APPROVED BY	DATE		STD. PLAN NO.
	NOVEMBER 2010		ST-220
TOWN ENGINEER			

# STREET



## TACTILE WARNING BAND (SECTION)

N.T.S.




## BEVELED LIP (SECTION)

N.T.S.

- (A) ALL CURB RAMPS SHALL COMPLY WITH THE AMERICAN DISABILITIES ACT.
- (B) CONCRETE CURB AND GUTTER, SEE STD. DETAIL 210.
- (C) CONCRETE VERTICAL CURB, SEE STD. DETAIL 211, IF NECESSARY.
- (D) CONCRETE SIDEWALK, SEE STD. DETAIL 216.
- (E) 3/8" EXPANSION JOINTS.
- (F) CURB RAMPS WILL NOT BE POURED INTEGRAL WITH SIDEWALK AND SHALL BE ISOLATED BY EXPANSION JOINT MATERIAL ON ALL SIDES, BUT NOT AT END OF RAMP ADJACENT TO ROADWAY.
- (G) EXPOSED SURFACES SHALL BE A MEDIUM BROOM FINISH. CURB RAMPS EXHIBITING A RUNNING SURFACE SLOPE FROM 5% TO 6.67% ARE REQUIRED TO HAVE A TRUNCATED DOME DETECTABLE WARNING SURFACE OVER THE FULL WIDTH AND DEPTH OF THE RAMP.
- (H) INSTALL 12" TACTILE WARNING BAND AROUND THE RAMP PERIMETER.
- (I) MAXIMUM SLOPES OF ADJOINING GUTTERS, THE ROAD SURFACE IMMEDIATELY ADJACENT TO THE CURB RAMP AND CONTINUOUS PASSAGE TO THE CURB RAMP SHALL NOT EXCEED 5% WITHIN 4' OF THE TOP OR BOTTOM OF THE CURB RAMP.

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		ST-221
TOWN ENGINEER			



TACTILE WARNING BAND (SECTION)

N.T.S.


BEVELED LIP (SECTION)

N.T.S.


- (A) ALL CURB RAMPS SHALL COMPLY WITH THE AMERICAN DISABILITIES ACT.
- (B) CONCRETE CURB AND GUTTER, SEE STD. DETAIL 210.
- (C) CONCRETE SIDEWALK, SEE STD. DETAIL 216. 4'0" MIN LANDING WITH A 2% MAX SLOPE.
- (D) 3/8" EXPANSION JOINTS.
- (E) CURB RAMPS WILL NOT BE POURED INTEGRAL WITH SIDEWALK AND SHALL BE ISOLATED BY EXPANSION JOINT MATERIAL ON ALL SIDES, BUT NOT AT END OF RAMP ADJACENT TO ROADWAY.
- (F) EXPOSED SURFACES SHALL BE A MEDIUM BROOM FINISH. CURB RAMPS EXHIBITING A RUNNING SURFACE SLOPE FROM 5% TO 6.67% ARE REQUIRED TO HAVE A TRUNCATED DOME DETECTABLE WARNING SURFACE OVER THE FULL WIDTH AND DEPTH OF THE RAMP.
- (G) SAWCUT AND REMOVE 18 IN. (MIN.) STREET SECTION FOR RAMP INSTALLATION.
- (H) CONCRETE VERTICAL CURB, SEE STD. DETAIL 211, IF NECESSARY.
- (I) INSTALL 12" TACTILE WARNING BAND AROUND THE RAMP PERIMETER.
- (J) MAXIMUM SLOPES OF ADJOINING GUTTERS, THE ROAD SURFACE IMMEDIATELY ADJACENT TO THE CURB RAMP AND CONTINUOUS PASSAGE TO THE CURB RAMP SHALL NOT EXCEED 5% WITHIN 4' OF THE TOP OR BOTTOM OF THE CURB RAMP.

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		ST-222
TOWN ENGINEER		CURB RAMP "CASE CM"	



ALTERNATE "A"





ALTERNATE "B"

NOTES:

- 1 ALL CURB RAMPS SHALL COMPLY WITH THE AMERICAN DISABILITIES ACT.
- 2 SEE STANDARD PLAN 220-222 FOR CURB RAMP TYPE

NOT TO SCALE

APPROVED BY	DATE	CURB RAMP TYPICAL LOCATIONS	STD. PLAN NO.
	NOVEMBER 2010		ST-223
TOWN ENGINEER			



**NOTES:**

1. Mortar joints between bricks to be 3/8".
2. Expansion joints as shown on plans.

"Villa Hermosa" theme: Depress concrete slab to receive brick strips 12" +/- wide. Mortar set flush with concrete. Grout joints flush. Center brick strips on trees and equally spaced between (10'+/-)


Install tree grates.

Install tooled score line 12 inches from panel edges.

**NOTE:**


All new paving to be "Villa Hermosa" as shown in this detail with the following exceptions:


A. Additional score lines at 45 degrees to be added as shown in detail below.




**NOTES:**

1. See Std. Detail 225 for Villa Hermosa sidewalk areas.
2. All concrete shall be Class "A", per Caltrans specifications, with 1 lb. (min.) lamp black per cubic yard.
3. ALL WORK SHALL CONFORM TO CURRENT A.D.A. REQUIREMENTS.

APPROVED BY	DATE		VILLA HERMOSA SIDEWALK	STD. PLAN NO.
	NOVEMBER 2010			ST-224
TOWN ENGINEER				



# LEGEND





## Downtown Commercial Areas

## Villa Hermosa Sidewalk Required

APPROVED BY	DATE		VILLA HERMOSA AREA	STD. PLAN NO.
<i>Kevin Rofau</i>	NOVEMBER 2010			ST-225
TOWN ENGINEER				

CONCRETE SIDEWALK  
SEE STD. PLAN 216






NOTES:


1. BRICKS FOR VILLA HERMOSA PATTERN CONCRETE SIDEWALK SHALL BE MCNEAR WIRE-CUT RED SOLID JUMBO BRICK (3 1/2" x 3 1/2" x 11 1/2") OR AS APPROVED BY THE ENGINEER. BULLNOSE BRICKS FOR PLANTERS SHALL BE MCNEAR WIRE-CUT RED CORED BULLNOSE JUMBO BRICK (2 7/16" x 3 7/8" x 11 1/2").
2. MORTAR SHALL CONFORM TO ASTM C270, TYPE "M" PROPERTY SPECIFICATION, WITH 2500 PSI MIN. AT 28 DAYS. OMIT LIME PUTTY IF PLASTIC TYPE CEMENT IS USED. COLOR OF MORTAR SHALL BE MEDIUM BROWN #641, TRUE TONE CEMENT COLORS BY DAVIS COLORS, (800) 356-4848. MORTAR AGGREGATE SHALL CONFORM TO ASTM C144. GROUT AGGREGATE SHALL CONFORM TO ASTM C404. HYDRATED LIME SHALL CONFORM TO ASTM C207.
3. CONTRACTOR SHALL SUBMIT BRICK, BULLNOSE BRICK, AND GROUT SAMPLES TO ENGINEER FOR APPROVAL.

NOT TO SCALE

APPROVED BY	DATE		CONCRETE JOINTS	STD. PLAN NO.
	NOVEMBER 2010			ST-226
TOWN ENGINEER				



1/4" STAINLESS STEEL SCREWS, FLUSH WHEN FINISHED



## NOTES:


1. MATERIAL FOR PEDESTRIAN HANDRAIL SHALL BE ALUMINUM (ASTM B 429).

NOT TO SCALE

APPROVED BY	DATE	PEDESTRIAN HANDRAIL	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-230

## NOTES:


1. FOLIAGE AT Maturity AND BERM, IF ANY, SHALL NOT EXCEED 3 FT IN HEIGHT.
2. A VISUAL CLEARANCE FROM THE STREET TO 15 FT IN HEIGHT SHALL BE MAINTAINED WITH ALL TREE FOLIAGE WITHIN THE SITE TRIANGLE.
3. A VISUAL CLEARANCE FROM THE SIDEWALK TO 7 FT IN HEIGHT SHALL BE MAINTAINED WITH ALL TREE FOLIAGE WITHIN THE SITE TRIANGLE.



### PUBLIC STREET POSTED SPEED LIMIT (MPH)

	MINIMUM DISTANCE (FT)
25	200
30	250
35	325
40	400


## PUBLIC STREET



NOT TO SCALE

APPROVED BY	DATE	<p>TOWN OF LOS GATOS ESTABLISHED 1856</p>	DRIVEWAY AND INTERSECTION SITE TRIANGLES	STD. PLAN NO.
	NOVEMBER 2010			ST-231
TOWN ENGINEER				

# CORNER SIGHT TRIANGLE




## NOTES:



For more information please read Town Code Section 26.10.065. Obstruction at corners of intersecting streets.

NOT TO SCALE

# TRAFFIC VIEW AREA



## NOTES:



For more information please read Town Code Section 23.10.080. Fences, walls, hedges and shrubs near street intersections, and Section 29.40.030. Fences, hedges and walls.



NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS ESTABLISHED 1852	STD. PLAN NO.
	NOVEMBER 2010		ST-232
TOWN ENGINEER		SIGHT TRIANGLE AND TRAFFIC VIEW AREA	

FRAME AND COVER  
NEENAH FOUNDRY CO.  
R-1973-1 OR APPROVED  
EQUAL OVER MONUMENT.  
FRAME AND COVER TO BE  
SET IN CONCRETE AFTER  
PAVING

SURVEYOR'S NOTE

EXACT POINT TO BE  
DETERMINED BY ACCURATE  
SURVEY AND CLEARLY  
PUNCHED IN TOP OF BRASS  
MARKER TOGETHER WITH  
SURVEYOR'S L.L.S. OR R.C.E.  
NUMBER IN 1/8" HIGH  
NUMERALS.




APPROVED BY	DATE	TOWN OF LOS GATOS	STREET CENTERLINE STANDARD MONUMENT	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				ST-233

# PLAN VIEW

## NOTES

PLANT TREES 4" HIGHER THAN DEPTH AT WHICH GROWN IN NURSERY. AVOID DAMAGE TO ROOTS. AVOID ROOTBALL WHEN PLACING STAKES.



APPROVED BY

DATE

NOVEMBER 2010

TOWN ENGINEER



TREE PLANTING  
DETAIL

STD. PLAN NO.

ST-234

## TREE SPECIFICATIONS

All 15 gal. trees must meet the following minimum specifications:


1. HEIGHT: 7 - 8 feet high planted in the ground.
2. CALIPER: 1-1/2 inches, measured 6 inches from the base.
3. BRANCHING NEED: Minimum spread of 2 - 3 feet.


Any exception to the above must be approved by the Town Arborist.

All planting stock must have the approval of the Town Arborist.

## PLANTING SEQUENCE



1. Dig the hole twice as large in diameter and 1-1/2 times as deep as the container in which the plant was delivered. Provide a 6 inch minimum clearance all around the rootball.
2. The existing soil area is to be removed to a depth of 2 feet and replaced with U.C. Ag. mix or approved equivalent. U.C. Ag. mix shall be combined with existing soil, 1/3 mix, 2/3 native soil.
3. Fill hole with the backfill mix to a level 1 inch below the curb.
4. Place 3 Agriform Planting Tablets per tree at equidistant spacing. Tablets shall be 21 grams each with a guaranteed test analysis of 20-10-5.
5. Remove the rootball carefully from the container by supporting it from below. Sever any circling roots (3/16 inch or greater) with sharp shears or knife. If the rootball is dense or compacted, carefully loosen the roots at the side and bottom of the rootball. Do not pull the rootball apart. The severing of large roots will encourage new roots initiating at the cuts.
6. Fill around the rootball with backfill and pack the soil with the shovel handle as you fill. Be careful not to disturb the rootball itself.
7. Use the remaining native soil to create a basin appropriate to the site.

APPROVED BY	DATE		TREE PLANTING SPECIFICATIONS	STD. PLAN NO.
	NOVEMBER 2010			ST-235
TOWN ENGINEER				ST-235



NOT TO SCALE

APPROVED BY	DATE		STD. PLAN NO.
	NOVEMBER 2010		ST-236
TOWN ENGINEER			FIXED BOLLARD






### NOTES:

1. DO NOT INSTALL 4" X 4" POST UNTIL CONCRETE IS COMPLETELY CURED.

NOT TO SCALE

APPROVED BY	DATE		STD. PLAN NO.
Rein Rofai	NOVEMBER 2010		
TOWN ENGINEER	REMOVABLE BOLLARD		ST-237





CONCRETE CURB & GUTTER, SEE STD. PLAN 210.

UNDISTURBED SUBGRADE OR APPROVED MATERIAL 95% MAX.  
COMPACTION ASTM D1557

4" CLASS II AGGREGATE BASE 95% MAX. COMPACTION ASTM D1557

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS	DRIVEWAY RECONSTRUCTION	STD. PLAN NO.
	NOVEMBER 2010			ST-238
TOWN ENGINEER				



APPROVED BY	DATE	SIGN MOUNTING DETAIL	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER		PLEASE SEE ST-240 FOR SIGN NOTES	ST-239

## NOTES:

- 1 SIDEWALKS AND PAVED AREAS SHALL BE CORE DRILLED BEFORE ATTEMPTING SIGN INSTALLATION.
- 2 SIGNS SHALL HAVE A MIN. HEIGHT OF 7' FROM THE NEAR EDGE OF SIGN TO THE SIDEWALK GRADE, OR TOP OF CURB, AND A 2' LATERAL CLEARANCE FROM THE FACE OF CURB TO THE NEAR EDGE OF SIGN. SIGN LOCATION SHALL BE AS SHOWN ON THE PLANS AND PER M.U.T.C.D.
- 3 REFLECTIVE SHEETING SHALL BE MANUFACTURED BY 3M TRAFFIC CONTROL MATERIALS DIVISION.
  - a. REGULATORY AND WARNING SIGNS SHEETING SHALL BE 3M DIAMOND GRADE VIP TYPE MATERIAL OR EQUIVALENT. SIZE OF SIGNS SHALL BE NO LESS THAN 30x30 UNLESS SPECIFIED BY THE TOWN ENGINEER.

## SIGN POST NOTES:

- 4 ALL TUBING MATERIAL SHALL BE "ULTI-MATE" SELECT PUNCH TYPE GALVANIZED STEEL (ASTM A70 GRADE 33) OR APPROVED EQUIVALENT. POST SHALL BE POWDER-COATED BLACK.
- 5 TUBING SHALL BE ROLL FORMED FROM STEEL CONFORMING TO STANDARD SPECIFICATIONS FOR STEEL SHEET, A.S.T.M. DESIGNATION A653-94, STRUCTURAL QUALITY, GRADE 50 MODIFIED TO GRADE 55.
- 6 MATERIAL SHALL BE HOT-DIP GALVANIZED (ZINC COATED), COATING DESIGNATION G-90, WITH ADDED CHEMICAL TREATMENT FOR ENHANCED CORROSION PROTECTION.
- 7 THE CROSS SECTION OF THE POST SHALL BE SQUARE TUBING, CAREFULLY FORMED FROM 14 GA. STEEL SHEET AND WELDED SO AS THE WELD FLASH DOES NOT INTERFERE WITH THE TELESCOPING PROPERTIES. SIZE OF POST SHALL BE 1.75" x 1.75".
- 8 HOLE DIAMETER SHALL BE 7/16" (PLUS OR MINUS 1/64") ON 1" CENTERS ON TWO OPPOSITE SIDES. HOLES SHALL BE ON CENTERLINE OF EACH SIDE IN TRUE ALIGNMENT AND OPPOSITE TO EACH OTHER. TOLERANCE ON THE HOLE SPACING IS PLUS OR MINUS 1/8" IN 20'. FIRST SET OF HOLES SHALL BE 1/2" FROM THE TOP OF THE ANCHOR. ANCHOR SHALL HAVE EITHER 6 OR 12 SETS OF HOLES. THE BOTTOM OF THE ANCHOR SHALL HAVE A PENETRATOR POINT.
- 9 CONCRETE SHALL BE POURED AROUND POST.

APPROVED BY	DATE		SIGN NOTES	STD. PLAN NO.
	NOVEMBER 2010			ST-240
TOWN ENGINEER				




Plate: .050 in. (min.) flat aluminum

Color: Brown with white border


Letters: 4 in. high, reflective white;

Helvetica, all capitals

Mounting Hardware: Center rod style;

2 plates per street name

APPROVED BY	DATE		PUBLIC STREET NAME SIGN	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				ST-241




### NOTES:

1. THE LOCATIONS OF SIGNS SHOWN ARE A GUIDELINE AND DEPEND ON FIELD CONDITIONS. VISIBILITY, OBSTRUCTION, UTILITIES, ETC. SHOULD BE CONSIDERED AT ALL TIME.

NOT TO SCALE

APPROVED BY	DATE		SIGN LOCATION	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				ST-242

PROJECT SIZE	LENGTH OF	
	CRUSHED ROCK	ATB
≤ 1/4 ACRE	30	0
≤ 1 ACRE	50	0
< 3 ACRE	100	0
> 3 ACRE	100	50





- (A) 4" CRUSHED ROCK WITH GEOTEXTILE MATERIAL UNDERNEATH.
- (B) THE MINIMUM LENGTH SHALL BE LENGTHENED AS NECESSARY TO ENSURE MATERIAL IS NOT TRACKED INTO THE PUBLIC RIGHT-OF-WAY. ALTERNATE CONSTRUCTION ENTRANCES WILL BE ALLOWED WITH APPROVAL OF THE CITY ENGINEER ON A CASE BY CASE BASIS, WHERE PHYSICAL SITE CONDITIONS AND SIZE DICTATE
- (C) ATB DRIVEWAY RAMP, OR SITE ACCESS ROAD 20' WIDE MIN. SEE TABLE ABOVE FOR REQUIRED LENGTH.
- (D) INSTALL ORANGE BARRIER FENCE TO DIRECT TRAFFIC ONTO CONSTRUCTION ENTRANCE
- (E) INSTALL 12" MIN. DIA. CULVERT IF A ROADSIDE DITCH IS PRESENT.

## NOTES:

- 1 SURFACE WATER - ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
- 2 MAINTENANCE - THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHT-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHT-OF-WAY MUST BE REMOVED IMMEDIATELY.
- 3 WHEELS SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO PUBLIC RIGHT-OF-WAY. WHEN WASHING IS USED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
- 4 PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.



NOT TO SCALE

APPROVED BY	DATE		STABILIZED CONSTRUCTION ENTRANCE	STD. PLAN NO.
	NOVEMBER 2010			ST-250
TOWN ENGINEER				





NOTES:

1. SILT FENCE SHALL BE CONSTRUCTED LONG ENOUGH TO EXTEND ACROSS THE EXPECTED FLOW PATH.
2. FILTER FABRIC SHALL BE PROPYLENE, NYLON, POLYESTER OR ETHYLENE YARN WITH A MINIMUM TENSILE STRENGTH OF 50 LBS. PER LINEAR FOOT AT 20 PERCENT MAXIMUM ELONGATION AND CONTAINING ULTRAVIOLET INHIBITORS. FILTER FABRIC SHALL RETAIN A MINIMUM OF 85% OF THE SOIL, BY WEIGHT, BASED ON SIEVE ANALYSIS, BUT IS NOT FINER THAN AN EQUIVALENT OPENING SIZE OF 70. WHEN STANDARD STRENGTH FABRIC IS USED, A WIRE MESH SUPPORT SHALL BE SECURELY FASTENED TO THE UPSLOPE SIDE OF POSTS.
3. SUPPORT POSTS SHALL BE A MINIMUM 4.5' LONG 2" X 4" WOOD POSTS OR T SECTION FENCE POSTS DRIVEN A MINIMUM OF 18 INCHES INTO THE GROUND. POSTS SHALL BE SPACED A MAXIMUM OF 6 FEET APART. FABRIC SHALL BE SECURELY FASTENED TO POSTS WITH 1 INCH STAPLES OR 16 GAUGE WIRE TIES SPACED A MAXIMUM OF 6 INCHES APART.
4. A 12 INCH FABRIC TRENCH SHALL BE EXCAVATED ALONG THE UPHILL SIDE OF SILT FENCE POSTS. THE BOTTOM EDGE OF THE FABRIC SHALL EXTEND TO AND ACROSS THE BOTTOM OF THE TRENCH. THE TRENCH SHALL BE BACKFILLED TO 4 INCHES ABOVE GROUND AND COMPACTED TO BURY AND SECURE THE BOTTOM OF THE FILTER FABRIC.
5. CONTRACTER SHALL MAKE INSPECTIONS WEEKLY DURING THE WET SEASON, MONTHLY DURING THE DRY SEASON AND IMMEDIATELY AFTER EACH RAINFALL TO DETERMINE IF REPAIRS AND SEDIMENT REMOVAL IS REQUIRED. SEDIMENT SHALL BE REMOVED BEFORE IT HAS REACHED ONE THIRD THE HEIGHT OF THE FILTER FABRIC.



APPROVED BY	DATE	SILT FENCE	
	NOVEMBER 2010		
TOWN ENGINEER		STD. PLAN NO.	ST-251




1. BALES SHALL BE PLACED WITH BINDINGS IN A HORIZONTAL POSITION. BALES SHALL BE TIGHTLY BOUND TOGETHER USING A MINIMUM OF 16 GA. WIRE OR TIE WRAPS TO TIE BINDINGS BETWEEN BALES. USE THE MINIMUM NUMBER OF BALES THAT PROVIDE PERIMETER COVERAGE WITHOUT COVERING ANY PORTION OF THE GRATE INLETS.
2. CONTRACTOR SHALL INSPECT BALES WEEKLY AND AFTER EACH RAINFALL TO DETERMINE IF REPAIR OR SEDIMENT REMOVAL IS REQUIRED. SEDIMENT SHALL BE REMOVED ON A REGULAR BASIS.
3. CONTRACTOR SHALL INSPECT BALES DAILY FOR PROPER PLACEMENT AROUND THE DRAIN INLETS.
4. BALES SHALL BE REPLACED WHEN THEY HAVE BEEN DAMAGED, COLLAPSED OR DECOMPOSED.

PLAN VIEW


NOT TO SCALE

APPROVED BY	DATE	ST. PLAN NO.
	NOVEMBER 2010	
TOWN ENGINEER		ST-252





ENTRENCHMENT DETAIL  
IN SLOPE AREA




ENTRENCHMENT DETAIL  
IN FLAT AREA

NOTES:


1. STRAW ROLL INSTALLATION REQUIRES THE PLACEMENT AND SECURE STAKING OF THE ROLL IN A TRENCH, 3" TO 4" DEEP.
2. ADJACENT ROLLS SHALL TIGHTLY ABUT.
3. RUNOFF MUST NOT BE ALLOWED TO RUN UNDER OR AROUND STRAW ROLL.
4. STRAW ROLLS SHALL BE PLACED ON SLOPES @ MAX. 25' SPACING.

NOT TO SCALE


APPROVED BY	DATE		STD. PLAN NO.
	NOVEMBER 2010		ST-253
TOWN ENGINEER			



PROFILE



PLAN



SECTION A-A

NOT TO SCALE

APPROVED BY	DATE	ENERGY DISSAPATOR	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-254

# INTERIM EROSION CONTROL MEASURES

(USE AS APPLICABLE TO YOUR PROJECT.)

## NOTES:

1. IT IS THE RESPONSIBILITY OF THE OWNER/CONTRACTOR TO INSURE THAT NO MUD OR SILTATION LEAVES THE PROJECT SITE.
2. INTERIM EROSION CONTROL MEASURES MUST BE COMPLETED AND IN PLACE BY OCTOBER 1.
3. ALL INTERIM EROSION CONTROL MEASURES MUST BE CONTINUOUSLY MAINTAINED THROUGHOUT THE OCTOBER 1 TO APRIL 15 RAINY SEASON.
4. CALL THE INSPECTION LINE AT (408) 399-5760 BY SEPTEMBER 15 FOR INSPECTION OF EROSION CONTROL DEVICES. CALL 24 HOURS IN ADVANCE. INCLUDE GRADING PERMIT NUMBER.
5. IF EROSION CONTROL MEASURES ARE NOT IN PLACE AS REQUIRED OR NOT MAINTAINED, ALL WORK SHALL CEASE UNTIL EROSION CONTROL MEASURES ARE REMEDIED.

## MEASURES:

1. INSTALL SILT FENCE. PROVIDE DETAIL, SHOW LOCATION ON PLANS AND ADD NOTES AS NEEDED.
2. SEED EXPOSED AREAS PER TOWN SPECIFICATIONS. SEE BELOW.
3. INSTALL DRAINAGE MEASURES INCLUDING CATCH BASINS, ENERGY DISSIPATORS, ETC. PROVIDE DETAIL, SHOW LOCATIONS ON PLANS, AND ADD NOTES AS NEEDED.
4. INSTALL CHECK DAMS, SEDIMENT TRAPS AND BASINS, TEMPORARY SWALES.
5. INSTALL JUTE NETTING OVER SEEDED AND MULCHED SLOPES.
6. COVER BARE SLOPES WITH STRAW BLANKETS.



## SEEDING SPECIFICATIONS:

1. SEED AND MULCH WILL BE APPLIED BY OCT 1 TO ALL DISTURBED SLOPES AND TO ALL CUTS AND FILL SLOPES WITHIN OR ADJACENT TO PUBLIC RIGHTS-OF-WAY AS DIRECTED BY TOWN ENGINEER.
2. SEED AND FERTILIZER WILL BE APPLIED HYDRAULICALLY OR BY HAND AT THE RATES SPECIFIED BELOW. ON SLOPES, STRAW WILL BE APPLIED BY BLOWER OR BY HAND AND ANCHORED IN PLACE BY PUNCHING OR WITH JUTE NETTING.


ITEM	POUNDS/ACRE
"Blando" brome	30
Annual rye grass	20
Fertilizer (16-20-0 & 15% sulfur)	500
Straw	4,000

3. SEEDED AREAS WILL BE REPAIRED, RESEEDED AND MULCHED, IF DAMAGED.


APPROVED BY	DATE		INTERIM EROSION CONTROL NOTES	STD. PLAN NO.
	NOVEMBER 2010			ST-255
TOWN ENGINEER				



APPROVED BY	DATE	 TOWN OF LOS GATOS	TEMPORARY CONCRETE WASHOUT FACILITY	STD. PLAN NO.
	NOVEMBER 2010			ST-256
TOWN ENGINEER				





PERSPECTIVE

APPROVED BY	DATE	TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		ST-257
TOWN ENGINEER			


1' SPACE WHITE TYP.  
1' WHITE, MARKING TYP.

**HUMP**

CENTER  
LINE



### **SECTION A-A**



### **NOTES:**

1. PLACE IN TWO LIFTS.
2. TYPE A A.C. AR-4000, MAXIMUM AGGREGATE SIZE 1/2".
3. GRIND TO KEY IN ALL EDGES (1.5" BY 12").
4. SIGNS SHOWN TYPICAL IN BOTH DIRECTIONS.
5. OPTIONAL FOR HUMPS WITHIN A SERIES.
6. SIGNS SHALL BE 3M DIAMOND GRADE.

### **SECTION B-B**

APPROVED BY

DATE

*Rein Rofai*

NOVEMBER 2010

TOWN ENGINEER




SPEED HUMP  
DETAIL

STD. PLAN NO.


ST-260

PAINTING OF THE CROSSWALK SHALL MEET CALTRANS' STANDARD SPECIFICATIONS.




NOT TO SCALE

APPROVED BY	DATE		CROSSWALK MARKING	STD. PLAN NO.
	NOVEMBER 2010			ST-261
TOWN ENGINEER				



1. THESE DIMENSIONS SHALL BE USED WHEN OVERHANG FROM FRONT VEHICLE WHEEL IS NOT PRESENT.
2. ALL STRIPING SHALL COMPLY WITH "OFF-STREET PARKING DOUBLE STRIPE" DETAIL 264 AND "ACCESSIBLE PARKING" DETAIL 265.
3. ALL OFF-STREET PARKING SHALL COMPLY WITH SECTION 29.10.155 OF THE LOS GATOS TOWN CODE.
4. WHEEL STOPS ARE NOT PERMITTED. CONTINUOUS CURBING MAY BE USED. NOT TO SCALE

APPROVED BY	DATE	OFF-STREET PARKING WITHOUT OVERHANG	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-262




**NOTES:**

1. THESE DIMENSIONS SHALL BE USED WHEN OVERHANG FROM FRONT VEHICLE WHEEL IS PRESENT.
2. ALL STRIPING SHALL COMPLY WITH "OFF-STREET PARKING DOUBLE STRIPE" DETAIL 264 AND "ACCESSIBLE PARKING" DETAIL 265.
3. ALL OFF-STREET PARKING SHALL COMPLY WITH SECTION 29.10.155 OF THE LOS GATOS TOWN CODE.
4. WHEEL STOPS ARE NOT PERMITTED. CONTINUOUS CURBING MAY BE USED.

NOT TO SCALE

APPROVED BY	DATE	OFF-STREET PARKING WITH OVERHANG	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-263




NOTES:

1. ALL OFF-STREET PARKING SHALL COMPLY WITH SECTION 29.10.155 OF THE LOS GATOS TOWN CODE.


NOT TO SCALE

APPROVED BY	DATE		OFF-STREET PARKING DOUBLE STRIPE	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				ST-264


ISA PARKING SIGN R99  
SEE NOTE 2



SINGLE PARKING SPACE



DOUBLE PARKING SPACES



DIAGONAL PARKING SPACES

#### Number of Accessible Parking:

TOTAL NUMBER OF PARKING SPACES OR STALLS	MINIMUM NUMBER OF DISABLED ACCESSIBLE PARKING SPACES OR STALLS	
1-25	1	
26-50	2	
51-75	3	
76-100	4	
101-150	5	
151-200	6	
201-300	7	
301-400	8	
401-500	9	
501-1000	2% OF TOTAL 20 + 1 FOR EACH 100 OR FRACTION THEREOF OVER 1001	
>1000		

TABLE A



APPROVED BY

*Rein Ropponi*

DATE

NOVEMBER 2010

TOWN ENGINEER

ACCESSIBLE  
PARKING  
(CBC Section 1129B)

STD. PLAN NO.

ST-265

PAVEMENT MARKING DETAIL  
SEE NOTE 7

NO  
PARKING

2"

1.6"


ISA MARKING FOR ACCESSIBLE PARKING SPACE OR STALL




ISA PARKING SIGN (R99)  
STANDARD 12" X 18"  
SEE NOTE 6



VAN  
ACCESSIBLE  
VAN ACCESSIBLE SIGN (R99A)  
STANDARD 12" X 8"  
SEE NOTES 2 AND 6



SIGN (R100B)  
STANDARD 18" X 24"  
SEE NOTE 10





DETAIL A  
ISA = INTERNATIONAL SYMBOL OF ACCESSIBILITY


**NOTES:**

1. ACCESSIBLE PARKING SPACES SERVING A PARTICULAR BUILDING SHALL BE LOCATED ON THE SHORTEST ACCESSIBLE ROUTE OF TRAVEL FROM ADJACENT PARKING TO AN ACCESSIBLE ENTRANCE. IN PARKING FACILITIES THAT DO NOT SERVE A PARTICULAR BUILDING, ACCESSIBLE PARKING SHALL BE LOCATED ON THE SHORTEST ACCESSIBLE ROUTE OF TRAVEL TO AN ACCESSIBLE PEDESTRIAN ENTRANCE OF THE PARKING FACILITY.
2. ONE IN EVERY EIGHT ACCESSIBLE OFF-STREET PARKING STALLS, BUT NOT LESS THAN ONE, SHALL BE SERVED BY AN ACCESSIBLE AISLE OF 8' MIN WIDTH AND SHALL BE SIGNED VAN ACCESSIBLE. THE R99A "VAN ACCESSIBLE" SIGN SHALL BE MOUNTED BELOW THE R99 "ISA PARKING" SIGN.
3. IN EACH PARKING STALL, A CURB OR BUMPER SHALL BE PROVIDED AND LOCATED TO PREVENT ENCROACHMENT OF VEHICLES OVER THE REQUIRED WIDTH OF WALKWAYS. PARKING STALLS SHALL BE SO LOCATED THAT PERSONS WITH DISABILITIES ARE NOT COMPELLED TO WHEEL OR WALK BEHIND PARKED VEHICLES OTHER THAN THEIR OWN.
4. SURFACE SLOPES OF ACCESSIBLE OFF-STREET PARKING STALLS SHALL BE THE MINIMUM POSSIBLE AND SHALL NOT EXCEED 2% IN ANY DIRECTION.
5. TABLE A SHALL BE USED TO DETERMINE THE REQUIRED NUMBER OF ACCESSIBLE PARKING STALLS IN ANY PARKING LOT OR GARAGE.
6. WHERE R99 "ISA PARKING" OR R99A "VAN ACCESSIBLE" SIGNS ARE INSTALLED ON SIDEWALKS OR OTHER PATHS OF TRAVEL, THE BOTTOM OF THE SIGN PANEL SHALL BE A MINIMUM OF 6'8" ABOVE THE SURFACE OF THE SIDEWALK OR PATH.
7. CURB RAMPS SHALL CONFORM TO THE STANDARD DETAIL 220-222.
8. BUILDING PERMIT(S) REQUIRED FOR NEW AND RESTRIPIING OF EXISTING PARKING LOTS.
9. THE WORDS "NO PARKING" SHALL BE PAINTED IN WHITE LETTERS NO LESS THAN 12" HIGH AND LOCATED SO THAT IT IS VISIBLE TO TRAFFIC ENFORCEMENT OFFICIALS.
10. A R100B SIGN SHALL BE POSTED IN A CONSPICUOUS PLACE AT EACH ENTRANCE TO OFF-STREET PARKING FACILITIES OR IMMEDIATELY ADJACENT TO AND VISIBLE FROM EACH STALL. THE SIGN SHALL INCLUDE THE ADDRESS WHERE THE TOWED VEHICLE MAY BE RECLAIMED AND THE TELEPHONE NUMBER OF THE LOCAL TRAFFIC LAW ENFORCEMENT AGENCY.
11. WHERE A SINGEL (NON-VAN) ACCESSIBLE PARKING SPACE IS PROVIDED, THE LOADING AND UNLOADING ACCESS AISLE SHALL BE ON THE PASSENGER SIDE OF THE VEHICLE AS THE VEHICLE IS GOING FORWARD INTO THE PARKING SPACE.
12. WHERE A VAN ACCESSIBLE PARKING SPACE IS PROVIDED, THE LOADING AND UNLOADING ACCESS AISLE SHALL BE 8' WIDE MINIMUM, AND SHALL ONLY BE ON THE PASSENGER SIDE OF THE VEHICLE AS THE VEHICLE IS GOING FORWARD INTO THE PARKING SPACE.

APPROVED BY	DATE		ACCESSIBLE PARKING NOTES (CBC Section 1129B)	STD. PLAN NO.
Rein Rofai	NOVEMBER 2010		ST-266	
TOWN ENGINEER				



DETAIL B  
PARKING T STENCIL  
(END STALL)




DETAIL A  
PARKING T STENCIL  
(TYPICAL)

NOTES:

1. TYPICAL PARALLEL PARKING STALL IS 8'-WIDE 22'-LONG. END PARKING STALL LENGTH MAY BE REDUCED TO 17' MINIMUM.
2. PARKING STALL WIDTH, IF APPROVED BY ENGINEER, MAY BE REDUCED TO 7' MINIMUM FOR NARROW LOW VOLUME MINOR STREETS TO MAINTAIN DESIRED TRAVEL LANE WIDTH.


NOT TO  
SCALE

APPROVED BY	DATE	TOWN OF LOS GATOS	ON-STREET PARKING T STRIPING DETAIL	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				ST-267



NOT TO SCALE

APPROVED BY	DATE	TEARDROP LIGHTING	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			ST-270




NOT TO SCALE


APPROVED BY	DATE	TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		ST-271
TOWN ENGINEER		STERNBERG LIGHTING	

FRAME AND GRATE

2" x 3/16" RETICULINE  
BARS (TYPICAL)



B




ANGLE ANCHOR

NOTE:

WHERE INLET IS LOCATED WITHIN A RETURN, ANGLE ANCHOR SHALL BE CURVED TO MATCH FACE OF CURB RADIUS.

PLAN



SECTION B - B

SECTION A - A

APPROVED BY

DATE

NOVEMBER 2010


TOWN ENGINEER



STANDARD CURB  
INLET


STD. PLAN NO.

SD-301




NOTE:

1. HINGED GRATE ONLY WHEN SPECIFIED.
2. PLACE GRATE BARS PARALLEL TO FLOW.
3. FRAME, GRATE AND ANCHORS SHALL BE GALVANIZED AFTER FABRICATION.
4. FRAME AND GRATE TO BE WELDED STEEL OR WRITTEN APPROVED ALTERNATIVE.




APPROVED BY	DATE	RETICULINE FRAME & GRATE	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SD-302


FRAME TO BE ANCHORED  
TO CONCRETE PER  
MANUFACTURER'S  
SPECIFICATIONS.



PLAN




SECTION A-A




SECTION B-B

APPROVED BY	DATE		CATCH BASIN	STD. PLAN NO.
	NOVEMBER 2010			SD-303
TOWN ENGINEER				



## MANHOLE & CATCHBASIN ADJUSTMENT



OUTSIDE PAVED AREA

INSIDE PAVED AREA


## VALVE BOX ADJUSTMENT

### NOTES:

NOT TO SCALE

1. REMOVE PAVEMENT AND BASE MATERIALS FOR A DISTANCE WHICH IS EQUAL TO THE DIAMETER OF THE FRAME PLUS TWO FEET. ADJUST CASTING FRAME TO NEW PAVEMENT SURFACE USING CONCRETE BLOCKS.
2. ASPHALT CONCRETE CLASS "B" (3" MIN.) REPLACEMENT PATCH TO BE 1" THICKER THAN PREVIOUSLY EXISTED. THE REST OF THE BACKFILL TO BE CONTROLLED DENSITY FILL.
3. 2"x4"x8" SOLID BRICK USED FOR FINAL ADJUSTMENT TO GRADE. 6" HIGH MAX.

APPROVED BY	DATE	MANHOLE/CATCH BASIN & VALVE BOX ADJUSTMENT	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SD-304



APPROVED BY

DATE

NOVEMBER 2010

TOWN ENGINEER



TRENCH DETAIL

STD. PLAN NO.

SD-305

BEDDING MATERIALGRANULAR BEDDING MATERIAL REQUIREMENTS  
CALTRANS DURABILITY INDEX MINIMUM 30

SIEVE SIZES	PERCENTAGE PASSING
1"	100
3/4"	90-100
3/8"	20-55
#4	0-10
#8	0-5


STRUCTURAL BACKFILLSTRUCTURAL BACKFILL REQUIREMENTS PERCENT  
PASSING MINIMUM SAND EQUIVALENT OF 20

SIEVE SIZES	PERCENTAGE PASSING
1-1/2"	100
3/4"	80-100
#4	30-60
#30	5-35
#200	0-12


NOTES:

- 1 ALL BACKFILL MATERIAL SHALL BE PLACED IN LIFTS NOT TO EXCEED 6 INCHES BEFORE COMPACTION UNLESS AUTHORIZED BY THE ENGINEER.
- 2 MECHANICAL COMPACTION OF BACKFILL MATERIAL SHALL NOT BEGIN UNTIL THE DEPTH OF COMPACTED BACKFILL MATERIAL IS 2 FEET ABOVE THE TOP OF PIPE.
- 3 EACH LIFT SHALL BE MECHANICALLY COMPACTED TO THE REQUIRED DENSITY PRIOR TO PLACING SUCCEEDING LIFTS OF BACKING MATERIAL.
- 4 COMPACTION TESTS SHALL BE AS REQUIRED BY THE TOWN CONSTRUCTION INSPECTOR, BUT IN NO CASE LESS THAN 2 TESTS EVERY 200 FT OF TRENCH. (ONE AT FINISH SUBGRADE AND ONE AT 50% OF TRENCH DEPTH).
- 5 IN-PLACE DENSITY WILL BE DETERMINED BY ONE OR MORE OF THE FOLLOWING METHODS. (A) ASTM D1557, TEST FOR DENSITY OF SOIL IN-PLACE BY THE SAND CONE METHOD. (B) ASTM D2922 - (NUCLEAR METHOD)
- 6 LABORATORY DENSITY WILL BE DETERMINED BY ASTM D1557, MOISTURE-DENSITY RELATIONS OF SOILS AND SOIL-AGGREGATE MIXTURES.
- 7 IF THE EDGE OF THE TRENCH FALLS WITHIN 3' OF THE GUTTER, THE ENTIRE PAVEMENT SHALL BE REMOVED TO THE GUTTER.
- 8 ON STEEP SLOPES, CONSTRUCT CLAY OR CONCRETE DAM THROUGH THE BEDDING MATERIAL AS DETERMINED BY TOWN ENGINEER.
- 9 FOR CONCRETE STREETS PLACE 6" CLASS A P.C.C. OVER 6" CLASS 2 A.B. FOR FINISHED SURFACE.
- 10 ALL TRENCH CONSTRUCTION SHALL BE IN COMPLIANCE WITH LATEST OSHA STANDARDS.
- 11 PLACE PERMANENT PAVEMENT WITHIN 30 DAYS AFTER BACKFILLING. INSTALL TEMPORARY AC TO FINISH GRADE UNTIL PERMANENT AC IS PLACED.
- 12 IF EXISTING AC SECTION IS LESS THAN 4", GRIND AC KEY TO FULL DEPTH OF EXISTING AC & REPLACE FULL DEPTH OF AC SECTION (3" MIN.)
- 13 IN PAVED STREETS, ALL CUTS SHALL BE SMOOTH & VERTICAL WITH THE AREA BEING GENERALLY RECTANGULAR. NATIVE MATERIAL MAY BE USED AS BACKFILL IF APPROVED BY TOWN ENGINEER. IF SAND BACKFILL IS USED, IT MUST BE WELL GRADED, TAMPED WITH VIBRATORY COMPACTOR & LIGHTLY JETTED, IF NECESSARY.
- 14 A SEMI-FINISHED SURFACE OF CUTBACK OR LOWERED CROSS-SECTION (MAX. LOWERED DEPTH, 1/2") OF ASPHALTIC CONCRETE WILL BE ALLOWED FOR A MAXIMUM OF 30 DAYS AFTER BACKFILLING TO ALLOW FOR SETTLING. CONTRACTOR SHALL PATCH ANY TIME THAT EXCESSIVE SETTLING OCCURS.
- 15 WITHIN 30 DAYS, CONTRACTOR SHALL RESTORE SURFACE TO ITS ORIGINAL CONDITION & BE RESPONSIBLE FOR ANY FURTHER SETTLING OR FAILURE FOR A MIN. OF 2 YEARS. IF CUTBACK IS USED AS A SEMI-FINISHED SURFACE, IT SHALL BE REMOVED BEFORE FINISHING. A 6" EDGE OF EXISTING AC SHALL BE REMOVED AROUND THE PERIMETER OF THE CUT BEFORE PLACEMENT OF ASPHALTIC CONCRETE.
- 16 A 6" COURSE OF CRUSHED ROCK BASE (1.5" MAX. AGGREGATE) & 3" ASPHALTIC CONCRETE IS MIN. SURFACING TO BE RESTORED. NO RESTORATION SHALL BE LESS SUBSTANTIAL THAN EXISTING COMPOSITION. IN CASES OF CONCRETE STREETS, A 6" THICKNESS OF CONCRETE ON A 6" ROCK CUSHION IS THE MINIMUM STANDARD.

APPROVED BY	DATE		TRENCH DETAIL NOTES	STD. PLAN NO.
	NOVEMBER 2010			SD-306
TOWN ENGINEER				




PLAN



SECTION A-A

NOT TO SCALE


APPROVED BY	DATE		PIPE OUT FALL DETAIL	STD. PLAN NO.
	NOVEMBER 2010			SD-307
TOWN ENGINEER				



### PLAN VIEW


NOT TO SCALE

APPROVED BY	DATE	 <b>OIL WATER SEPARATOR LAYOUT</b>	STD. PLAN NO.
	NOVEMBER 2010		SD-308
TOWN ENGINEER			



PLAN

- (A) INSTALL MANHOLE FRAME AND COVER, SEE STD. PLAN 302
- (B) STEPS.
- (C) SEE PLAN AND SPECIFICATIONS FOR SIZE AND TYPE OF PIPE ENTERING AND EXITING CB. AND INVERT ELEVATIONS.
- (D) 54" TYPE II CB. OR LARGER. 72" MIN. FOR WET PONDS.
- (E) WET POND/VULT INLET WITH SHEAR GATE OR A FLAP GATE.




NOTES:

1. THE CROWN OF THE VAULT INLET SHALL BE AT OR BELOW THE INVERT ELEVATION OF THE BYPASS PIPE.
2. THIS DETAIL IS A SCHEMATIC REPRESENTATION ONLY. ACTUAL CONFIGURATION WILL VARY DEPENDING ON SPECIFIC SITE CONSTRAINTS AND APPLICABLE DESIGN CRITERIA.


ELEVATION

NOT TO SCALE


APPROVED BY	DATE	 TOWN OF LOS GATOS INCORPORATED 1852	STD. PLAN NO.
	NOVEMBER 2010		SD-309
TOWN ENGINEER			



PLAN-BASE



PLAN-COVER




SECTION A-A

SECTION B-B


NOT TO SCALE

APPROVED BY	DATE	TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SD-310




THIS SHOWS A TYPICAL DETENTION SYSTEM ON A SITE, ACCEPTABLE LOCATIONS FOR THE DETENTION PIPE, CONNECTIONS OF DOWNSPOUTS, CATCHBASINS AND DISCHARGE OF THE WATER ONTO A NATURAL LOCATION MUST BE APPROVED BY THE TOWN ENGINEER.

APPROVED BY	DATE	DETENTION/ INFILTRATION SYSTEM FOR SMALL PROJECTS	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SD-311



## FLOW CONTROL DEVICE




## FLOW CONTROL STRUCTURE

### NOTES:


- 1 OVERFLOW AND OUTLET PIPES HAVE SAME DIAMETER, 4" MIN.
- 2 THIS DESIGN IS ONLY APPROVED FOR PROPERTY WITH LESS THAN 5,000 SQUARE FEET OF IMPERVIOUS SURFACE.

NOT TO SCALE


APPROVED BY	DATE	TOWN OF LOS GATOS	CONTROL STRUCTURE FOR SMALL PROJECTS	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				SD-312



OPTION 1




OPTION 2



NOT TO SCALE

APPROVED BY	DATE		BUILDING/YARD DRAIN DETAIL	STD. PLAN NO.
	NOVEMBER 2010			SD-314
TOWN ENGINEER				

MANHOLE FRAME AND  
COVER, SEE STD PLAN 316.




NOTES:

1. PRECAST M.H. SECTIONS SHALL CONFORM TO APPLICABLE PROVISIONS OF ASTM C478.
2. 9" CLASS II FOR AGGREGATE BASE BEDDING COMPAKTED TO 95% MAX. ASTM D1557.
3. STEPS SHALL BE GALV. STEEL 3/4" DIA., INSERTED 3" MIN.
4. ALL JOINTS WITH FLEXIBLE PLASTIC JOINT COMPOUND (RAM-NECK, QUICK SEAL, OR EQUAL). TWO LAYERS MAY BE REQUIRED TO SEAL BASE. PLASTER WITH MORTAR THEREAFTER.
5. MANHOLE BASE MUST BE POURED AGAINST UNDISTURBED SOIL. IF EXCAVATED TOO DEEP, FILL WITH CONCRETE.


NOT TO SCALE

APPROVED BY	DATE		STANDARD MANHOLE	STD. PLAN NO.
	NOVEMBER 2010			SD-315
TOWN ENGINEER				



COVER  
DIAMOND DETAIL PATTERN

PLAN



NOT TO SCALE


APPROVED BY	DATE	MANHOLE FRAME AND COVER	STD. PLAN NO.
	NOVEMBER 2010		SD-316
TOWN ENGINEER			



SET HYD. WITH 1/4" RAKE PER FOOT

## NOTES:

1. FOR CLOSE COUPLED HYDRANTS USE ALL FLANGE TYPE CONNECTIONS.
2. IF HYDRANT RISES THROUGH CONCRETE USE EXPANSION STRIP AROUND HYDRANT BARREL.
3. HYDRANT SHALL BE PAINTED TO COLOR ESTABLISHED BY FIRE CHIEF.



APPROVED BY

DATE

STD. PLAN NO.


NOVEMBER 2010



TOWN ENGINEER

FIRE HYDRANT

WA-500




**NOTES:**


1. CORPORATION STOPS SHALL BE FORD F700, 1 INCH OR EQUAL
2. WATER SERVICE SHALL BE 5' FROM LOT CORNERS

NOT TO SCALE

APPROVED BY	DATE	 TOWN OF LOS GATOS ESTABLISHED 1852	STD. PLAN NO.
	NOVEMBER 2010		WA-501
TOWN ENGINEER			




### CASE "A" HOOK UP TO OPEN BELL




### CASE "B" HOOK UP TO FLANGE OF MAIN VALVE

NOT TO SCALE

APPROVED BY	DATE		PRESSURE TEST DETAIL	STD. PLAN NO.
	NOVEMBER 2010			WA-502
TOWN ENGINEER				




APPROVED BY	DATE	TOWN OF LOS GATOS	TYPICAL VACUUM/AIR RELEASE VALVE	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				WA-503



HEIGHT OF BOX SHALL BE 12"

PLAN VIEW




RISER BOX

NOT TO SCALE

APPROVED BY	DATE		STD. PLAN NO.
	NOVEMBER 2010		WA-504
TOWN ENGINEER			




# ECLIPSE NO. 88 SAMPLING STATION




## NOTES:

1. SAMPLING STATIONS SHALL HAVE A 3/4" FIP INLET, AND A (3/4" HOSE OR UNTHEADED) NOZZLE.
2. ALL STATIONS SHALL BE ENCLOSED IN A LOCKABLE, NONREMOVABLE, ALUMINUM-CAST HOUSING.
3. WHEN OPENED, THE STATION SHALL REQUIRE NO KEY FOR OPERATION, AND THE WATER WILL FLOW IN AN ALL BRASS WATERWAY.
4. ALL WORKING PARTS WILL ALSO BE OF BRASS AND BE REMOVABLE FROM ABOVE GROUND WITH NO DIGGING. EXTERIOR PIPING SHALL BE GALVANIZED STEEL (BRASS PIPES ALSO AVAILABLE).
5. A COPPER VENT TUBE WILL ENABLE EACH STATION TO BE PUMPED FREE OF STANDING WATER TO PREVENT FREEZING AND TO MINIMIZE BACTERIA GROWTH.
6. ECLIPSE NO. 88 SAMPLING STATION SHALL BE MANUFACTURED BY KUPFERLE FOUNDRY, ST. LOUIS, MO 63102 OR EQUAL.


APPROVED BY	DATE	TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		WA-505
TOWN ENGINEER		SAMPLING STATION	



APPROVED BY	DATE	THRUST BLOCK	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			WA-506



PLAN




PROFILE

MATERIAL LIST:

1. OS&Y GATE VALVE W/HANDWHEEL FL X FL
2. DOUBLE (DSHS APPROVED) CHECK DETECTOR CHECK VALVE FL X FL
3. POST INDICATOR VALVE
4. 3/4" BALL VALVE (TEST COCK)
5. CLASS 52 DI WALL PIPE FL X FL
6. CLASS 52 DI 90° BEND FL X FL
7. CLASS 52 DI TEE FL X FL
8. SWING CHECK VALVE W/BALL DRIP ASSEMBLY
9. FIRE DEPARTMENT CONNECTION
10. VALVE STANDS
11. WHERE PIPING PASSES THROUGH CONCRETE WALL PROVIDE 2" CLEARANCE W/ WATERPROOF MASTIC OR FLEXIBLE SEALANT


FIRE DEPARTMENT CONNECTION (FDC)



GENERAL NOTES:


- A. PIPE FROM VAULT TO BUILDING SHALL BE CLASS 50 DI.
- B. TAMPER SWITCHES SHALL BE INSTALLED ON 1 AND 3 CONNECTED TO BUILDING FIRE ALARM SYSTEM.
- C. INSTALL PLUGS ON ALL TEST COCKS. FINGER TIGHTEN.
- D. ALL PIPING SHALL BE A MINIMUM OF 4" DIA. AS PER NFPA13.


APPROVED BY	DATE	TOWN OF LOS GATOS	DOUBLE CHECK VALVE ASSEMBLY WITH/FDC	STD. PLAN NO.
	NOVEMBER 2010			WA-507
TOWN ENGINEER				



SEE STD. PLAN 501 FOR DETAILS

NOT TO SCALE

APPROVED BY	DATE	TOWN OF LOS GATOS	STD. PLAN NO.
	NOVEMBER 2010		WA-508
TOWN ENGINEER			



APPROVED BY

DATE

NOVEMBER 2010


TOWN ENGINEER



TYP. INSTALLATION  
OF BACKFLOW  
PREVENTION  
ASSEMBLY

STD. PLAN NO.


WA-509







## NOTES:

1. DROP TEE TO BE INSTALLED MINIMUM OF 3' BELOW CONE SECTION.
2. INSIDE DROP MANHOLE SHALL BE INSTALLED ONLY WHERE APPROVED BY THE TOWN ENGINEER.

NOT TO SCALE

APPROVED BY	DATE	INSIDE MANHOLE DROP CONNECTION	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SS-603



OUTSIDE PAVED AREA


4" CLASS II AGGREGATE BASE

2" AC (TYPE A)

FINISHED GRADE

6" GRAVEL BORROW  
12" CONCRETE CLASS B

TRENCH DEPTH VARIES



TRENCH BOTTOM  
BEDDING AS REQUIRED

NOTES:

1. ALL SEWER PIPE SHALL BE ASTM 3034 SDR 35.
2. THE COVER SHALL BE LOCKING TYPE.

NOT TO SCALE

APPROVED BY

DATE

NOVEMBER 2010


TOWN ENGINEER




SEWER CLEANOUT

STD. PLAN NO.

SS-604




TYPICAL CURVED  
BASE




TYPICAL BASE  
WITH 2  
BRANCHES

NOTE:

"U" SHAPED CHANNEL MAY BE FORMED IN MANHOLE BASE  
OR CONSTRUCTED BY LAYING PIPE THROUGH THE BASE AND  
BREAKING OUT THE TOP HALF OF PIPE AND FORMING  
REMAINDER OF "U" SHAPED CHANNEL IN CONCRETE.



TYPICAL BASE  
WITH 1 BRANCH




TYPICAL STRAIGHT  
THROUGH BASE



NOT TO SCALE

APPROVED BY	DATE	MANHOLE BASE SECTIONS	STD. PLAN NO.
	NOVEMBER 2010		SS-605
TOWN ENGINEER			






### DEEP SEWER - GREATER THAN 10'



APPROVED BY	DATE	TOWN OF LOS GATOS	SANITARY SEWER LATERAL CONNECTIONS	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				SS-606



ZURN Z-1095 Backflow Preventer with Flapper

Dimensions in inches

A = 4 , B = 6 , E = 5 5/8 , G = 8 1/2 ,  
 J = 6 3/4 , K = 4 1/8


Note: The body shall be duracoated cast iron with Bronze threaded cover, automatic type valve seat and flapper which hangs closed during periods of non-operation.

All basements shall have a backflow preventor installed on their sewer line.


NOT TO SCALE

APPROVED BY	DATE		BACKFLOW PREVENTOR	STD. PLAN NO.
	NOVEMBER 2010			SS-607
TOWN ENGINEER				


TRAFFIC RATED PHOENIX  
IRON WORKS MH FRAME AND  
COVER #P-1090 MARKED  
"SANITARY SEWER" (TYP.)



**PLAN VIEW**



**LONGITUDINAL TANK CROSS SECTION**



NOTE:

TANK SHALL BE A TWO COMPARTMENT PRECAST CONCRETE TANK WITH THREE MANHOLES AND GAS-TIGHT LIDS. THE SEDIMENT COMPARTMENT SHALL HAVE 1250 GAL. CAPACITY AND THE EFFLUENT COMPARTMENT SHALL HAVE 750 GAL. CAPACITY.

**TYPICAL TANK CROSS SECTION**

NOT TO SCALE

APPROVED BY

DATE

NOVEMBER 2010




TOWN ENGINEER

**SINGLE FAMILY  
SEPTIC TANK  
EFFLUENT PUMPING  
(STEP) SYSTEM**

STD. PLAN NO.


SS-608



NOTES:


- 1) LOCATION OF ALL SANITARY FACILITIES SHALL BE SUBJECT TO DISTRICT APPROVAL.
- 2) PROVIDE VEHICLE ACCESS TO GRINDER PUMP/STEP SYSTEM.
- 3) AN EASEMENT SHALL BE GRANTED TO THE DISTRICT FOR VEHICULAR INGRESS/EGRESS AND FOR MAINTENANCE PURPOSES.
- 4) #8 GAUGE COPPER WIRE FOR TRACING PURPOSES SHALL BE PLACED ON ALL NEW LATERALS/DISCHARGE LINES.
- 5) CONTRACTOR SHALL SUBMIT PUMP INFORMATION PRIOR TO INSTALLATION.

APPROVED BY	DATE	TOWN OF LOS GATOS	TYPICAL STEP/GRINDER PUMP SYSTEM	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				SS-609




### **PUMP DETAIL**

NOT TO SCALE



TOP VIEW  
RISER ASSEMBLY


APPROVED BY	DATE	PUMP DETAIL-SINGLE FAMILY SEPTIC TANK EFFLUENT PUMP (STEP) SYSTEM	STD. PLAN NO.
	NOVEMBER 2010		
TOWN ENGINEER			SS-610



NOTES:

1. Pump shall be Environment One Model GP 2010-74 with poured-in-place concrete anchor. (2773 Balltown Road, Schenectady, NY 12309-1090. (518) 346-6161, Fax (518) 346-6188. SHAPE Inc. (925) 485-6085)
2. Pump shall be installed per manufacturer's recommendations.
3. See Single Family Grinder Pump Information Detail for pump anchor detail.
4. See 1-1/4 Inch Lateral Check Valve Station Detail for discharge line valve requirements.
5. Contractor shall supply District with handle to turn PVC ball valve.
6. Control Panel (supplied by ISAC (as per detail)).


APPROVED BY	DATE		SINGLE FAMILY GRINDER PUMP INSTALLATION DETAIL	STD. PLAN NO.
	NOVEMBER 2010			SS-611
TOWN ENGINEER				



NOTES:

1. CONTRACTOR SHALL SUPPLY DISTRICT WITH 4'-5' VALVE ACTUATOR  
HANDLE TO TURN VALVE.
2. ALL HDPE JOINTS SHALL BE FUSED.
3. TRACE WIRE SHALL BE CONTINUOUS #8 COPPER WITH 2 FEET COILED IN BOX.
4. RISER SHALL BE SAME SIZE AS FORCEMAIN.


APPROVED BY	DATE	TOWN OF LOS GATOS	CLEANOUT 2"-3" FORCEMAIN (STEP & GRINDER PUMP SYSTEMS)	STD. PLAN NO.
	NOVEMBER 2010			
TOWN ENGINEER				SS-613



NOTES:

1. CONTRACTOR SHALL SUPPLY DISTRICT WITH 4'-5' VALVE ACTUATOR HANDLE TO TURN VALVE.
2. ALL HDPE JOINTS SHALL BE FUSED.
3. TRACE WIRE SHALL BE CONTINUOUS #8 COPPER WITH 2 FEET COILED IN BOX.
4. RISER SHALL BE SAME SIZE AS FORCEMAIN.

APPROVED BY	DATE	TOWN OF LOS GATOS	CLEANOUT 2"-3" FORCEMAIN (STEP & GRINDER PUMP SYSTEMS)	STD. PLAN NO.
	NOVEMBER 2010			SS-613
TOWN ENGINEER				




NOTES:

1. TRACE WIRE SHALL BE CONTINUOUS #8 COPPER WIRE.
2. THE CONTRACTOR SHALL EXCAVATE BY HAND EXPOSING THE EXISTING PRESSURE SEWER MAIN.

APPROVED BY	DATE	 TOWN OF LOS GATOS <small>ESTABLISHED 1856</small>	STD. PLAN NO.
	NOVEMBER 2010		SS-614
TOWN ENGINEER			

NON TRAFFIC TRAFFIC



APPROVED BY

DATE

NOVEMBER 2010

TOWN ENGINEER




AIR RELEASE ASSEMBLY FOR STEP MAIN

STD. PLAN NO.

SS-615

CHRISTY CONCRETE PRODUCTS  
U52 GRADE RING WITH VAULT  
FRAME 36"x48"x3' DEEP  
T52-51JH TRAFFIC COVER  
OR EQUAL



NOTES:

PIPE, FITTINGS AND VALVES TO BE POLYETHYLENE

APPROVED BY

DATE

NOVEMBER 2010

TOWN ENGINEER




CLEANOUT PIT AT  
FORCE MAIN

STD. PLAN NO.

SS-616

TELEMETRY/CONTROL PANEL  
(BY INTEGRATED SYSTEMS  
AND CONTROL)



TELEMETRY/CONTROL  
PANEL ALARMS:

- HIGH WATER
- LOW WATER
- POWER FAIL
- ENTRY ACKNOWLEDGMENT
- BATTERY LOW

4"x4" PRESSURE TREATED

5'

2" CONDUIT

2-1" CONDUITS

3000 PSI CONCRETE

1'

2" CONDUIT  
TO PUMPS

1'-6"  
DIAMETER

FEATURES:

- PUMP STARTS (METERS)
- PUMP RUN TIMES (METERS)
- RETENTION MANAGEMENT
- LEVEL MONITORING
- REMOTE OVERRIDE CAPABLE

NOTES:

- 1) THE PANEL IS TO CONTROL THE PUMPS AND TO NOTIFY WEST BAY SANITARY DISTRICT SHOULD A MALFUNCTION OCCUR.
- 2) THE PROPERTY OWNER SHALL PROVIDE A PHONE LINE FOR THE PANEL. THE PHONE LINE'S SINGLE PURPOSE SHALL BE FOR TELEMETRY PANEL USE.
- 3) CONTROL/TELEMETRY PANEL SHALL BE SUPPLIED, APPROVED, AND CERTIFIED BY INTEGRATED SYSTEMS AND CONTROL (ISAC). (530) 878-9038.
- 4) LOCATION SUBJECT TO DISTRICT APPROVAL.
- 5) BURIED CONDUIT SHALL BE PVC SCHEDULE 40. EXPOSED CONDUIT SHALL BE GALVANIZED STEEL OR ALUMINUM.
- 6) CONTROL PANEL MUST BE SUPPLIED WITH HAND-OFF-AUTO SWITCH AND HOUR METERS. WITH HAND-OFF-AUTO SWITCH AND

APPROVED BY

DATE

NOVEMBER 2010



TOWN ENGINEER

CONTROL /  
TELEMETRY PANEL

STD. PLAN NO.

SS-617